

MicrodeviseMaster also provide microwave filters and other microwave components. in terms of function, low-pass, high-pass, band-pass, and band-reject filters; and in terms of structure, LC, cavity, ceramic, waveguide, tubular, helical, and microstrip filters. Other passive products produced include frequency dividers/combiners, duplexers, multiplexers, and equalizers. Using a full set of imported automatic production equipment, committed to mature technology, stable quality, good service and low prices to customers to improve competitive semiconductor products and services. A large number of spot supply, variety complete, quality assurance, we has a strong engineering team can provide technical support.

PRODUCTION CAPACITY OF LC FILTER STANDARD

Bandpass

X Features

Cover the 0.5MHz to 4GHz Frequency Range

3dB BW Available from 3% to 40%

Designs Available in 2~10 sections

05dB Chebyshev Response

X Specifications

Freq (MHz)	3dB% BW	VSWR	AVG Power (W)	Impedance (Ω)	No. of Sections	Shock	Vibration	Temp	Rel Humidity
0. 5-4000	3-40	1.5:1	1	50	2-10	20G	10G 10Hz-2000Hz	-40-+70°C	0-90%

Please contact us for up 4GHz

X Naming

<u>C1B</u>	-	<u>B</u>	<u>500</u>	<u>U</u>	<u>35</u>	-	<u>7</u>	<u>s</u>	/	<u>s</u>
1		2	3	4	5		6	7		8
			<u>Description</u>							
			Case code							
	2			B-Bandpass						
			Center frequency (MHz)							

Web:https://microdevicemaster.com	<u>Tel:+86-13588737685</u>	Email:sales@microdevicemaster.com	- 3 -
4		Supplemental codes	
5		Bandwidth (MHz)	
6		Number of sections	
7		Input connector	
8		Output connector	

Supplemental codes						
Н	0.5dB Bandwidth					
U	1dB Bandwidth					
Т	3dB Bandwidth					

Lowpass

X Features

Cover the 5MHz to 6GHz Frequency Range 3dB BW Available from 3% to 40%

Designs Available in 2~10 sections

05dB Chebyshev Response

X Specifications

Freq (MHz)	VSWR	AVG Power (W)	Impedance (Ω)	No. of Sections	Shock	Vibration	Temp	Rel Humidity
5-6000	1.5:1	1	50	2-10	20G	10G 10Hz-2000Hz	-40-+70°C	0-90%

X Naming

<u>C1B</u>	-	<u>L</u>	<u>500</u>	<u>U</u>	-	<u>7</u>	<u>S</u>	/	<u>S</u>	
1		2	3	4		5	6		7	
Co	<u>de</u>		<u>Description</u>							
1	1		Case code							
2 L-Lowpass										
3			Cutoff frequency (MHz)							

Web:https://microdevicemaster.com	Tel:+86-13588737685	Email:sales@microdevicemaster.com
-----------------------------------	---------------------	-----------------------------------

4	Supplemental codes
5	Number of sections
6	Input connector
7	Output connector

Connector	Code
SMA Female	S
SMA Male	R
Pins	Р

CONTACT US

MOB: +86-13588737685

MOB: +86-18758874480

E-mail: sales@microdevicemaster.com

E-mail: edwin@microdevicemaster.com

WEB: https://microdevicemaster.com

CHINA PRECISION MICRO DEVICES SUPPLIER

MDM Business Office:

No.2202, Jiangnan no.1 Building, Economic Development Zone, Xiaoshan District, Hangzhou City, zhejiang provice, China

